



## Declaration of Performance

EU Regulation No 305/2011, Annex III

DOP Number: 523

Revision: a

Product type: SC24

Intended use: To be used in walls and partitions, as an ancillary components for masonry  
(BSEN 1993-1-3 Structural Class III, intended to be used as a element that only transfers loads to the structure)

Manufacturer:

Harvey Steel Lintels  
Commerce way, Whitehall Industrial Estate  
Colchester, Essex CO2 8HH

The Notified Testing Laboratory:

University of Glamorgan Commercial Services Centre for Engineering,  
Research and Environmental Applications (CEREA)  
Llantwit Road, Treforest Pontypridd, CF37 1DL

Assessment and Verification of Constancy of Performance: System 3

This DOP is covered by following harmonised standard:

Manufactured according to the requirements of the European Harmonised Standard EN 845-2: 2003 and fulfil the conditions for UKAS Marking in accordance with annex ZA of EN 845-2: 2003.  
European Harmonised Standard EN 1090-1 :2009+A1:2011 and fulfil the conditions for UKAS Marking in accordance with annex ZA of EN 1090-1:2009  
The conformity assessment was executed in accordance with the method stated in tables ZA.2 and ZA.3 of the above standards. Factory Production Control Certificate GB16/871495 refers

Declared Performance:

Essential Characteristics	Performance
Load Bearing Capacity ( $E_k$ , in kN)	Given in TableA1 as safe working loads (SWL) under uniform distributed loading (UDL)
Deflection Under Load	Less than effective span/325 as safe working load in service limit state (EN 1990: 2002 + A1 ; 2005 NA)
Water Absorption	Zero
Water Vapour Permeability	Not Applicable
Thermal Resistance	Steel 64 W / m.k
Resistance to Fire	NPD (Contact Harvey steel for project specific details) document A
Durability (against corrosion)	Coating L14
Durability (against freeze/thaw)	Resistant
Dangerous Substance	None
Minimum Bearing Length (mm)	150 mm

Nominal Height (mm)	235.0
Mass per unit area ( $\text{kg/m}^2$ )	NPD
Mass ( $\text{kg/m}$ )	11.5-12.8
Load Ratio	-

**hEN**

EN 845 - 2 : 2012, Specification for ancillary components for masonry - Part 2: Lintels

**TableA1:**  
**Load bearing capacity**

Clear Opening span (mm)	SWL UDL (kN)
600	48
750	48
900	48
1050	48
1200	48
1350	48
1500	48
1650	48
1800	48
1950	45.5
2100	42.5
2250	39.8
2400	37.5
2550	35.4
2700	33.5
2850	31.9
3000	30.3
3150	29
3300	27.7
3450	26.5
3600	25.5
3750	24.5
3900	23.6
4050	22.4
4200	20.8
4350	19.4
4500	18.1

**Note:**

Issued under the sole responsibility of Harvey steel Lintels

Signed on behalf of the manufacturer by :

Michael Polley (General Manager)

Harvey Steel 01.01.2025

(Place and date of issue)